


## KOMPAKT

**6x19 Seale + IWRC, VERDICHTET,  
in Anl. an EN 12385-4,  
Kreuzschlag, 1960 N/mm<sup>2</sup>**


| Seil-Ø<br>mm | MBK<br>kN | kg    |
|--------------|-----------|-------|
| 6,00         | 34,2      | 19,6  |
| 7,00         | 44,7      | 25,6  |
| 8,00         | 56,5      | 32,4  |
| 9,00         | 76,9      | 44,1  |
| 10,00        | 92,3      | 52,9  |
| 11,00        | 109       | 62,5  |
| 12,00        | 127       | 72,9  |
| 13,00        | 147       | 84,1  |
| 14,00        | 168       | 96,1  |
| 15,00        | 179       | 102,4 |
| 16,00        | 226       | 130,0 |
| 18,00        | 279       | 160,0 |
| 20,00        | 338       | 194,0 |
| 22,00        | 402       | 237,0 |



## GRIZZLY

**6x25 Filler +IWRC, VERDICHTET,  
in Anl. an EN 12385-4,  
Kreuzschlag, 1960 N/mm<sup>2</sup>**


| Seil-Ø<br>mm | MBK<br>kN | Gewicht/100 m<br>kg |
|--------------|-----------|---------------------|
| 8,00         | 56,5      | 32,4                |
| 9,00         | 76,9      | 44,1                |
| 10,00        | 92,3      | 52,9                |
| 11,00        | 109       | 62,5                |
| 12,00        | 127       | 72,9                |
| 13,00        | 147       | 84,1                |
| 14,00        | 168       | 96,1                |
| 15,00        | 179       | 102,4               |
| 16,00        | 226       | 130,0               |
| 18,00        | 279       | 160,0               |



## KOMPAKT-PREMIUM

6x19 Seale + IWRC, VERDICHTET,  
in Anl. an EN 12385-4,  
Kreuzschlag, 2160 N/mm<sup>2</sup>

| Seil-Ø<br>mm | MBK<br>kN | Gewicht/100 m<br>kg |
|--------------|-----------|---------------------|
| 8,00         | 71,3      | 36,1                |
| 9,00         | 87,1      | 44,1                |
| 10,00        | 104,4     | 52,9                |
| 11,00        | 123,4     | 62,5                |
| 12,00        | 143,9     | 72,9                |
| 13,00        | 166,0     | 84,1                |



## GRIZZLY-PREMIUM

6x25 Filler +IWRC, VERDICHTET,  
in Anl. an EN 12385-4,  
Kreuzschlag, 2160 N/mm<sup>2</sup>

| Seil-Ø<br>mm | MBK<br>kN | Gewicht/100 m<br>kg |
|--------------|-----------|---------------------|
| 8,00         | 71,3      | 36,1                |
| 9,00         | 87,1      | 44,1                |
| 10,00        | 104,4     | 52,9                |
| 11,00        | 123,4     | 62,5                |
| 12,00        | 143,9     | 72,9                |
| 13,00        | 166,0     | 84,1                |